

FARM SPECIAL - Specificații tehnice



Descriere

FARM SPECIAL este o anvelopă de tractor potrivită pentru operațiunile de cultivare a solului. Carcasa puternică oferă un nivel ridicat de rezistență la perforare și o durată de viață mai lungă, în timp ce muchiiile rotunjite previn deteriorarea solului asigurând protecția culturilor valoroase. FARM SPECIAL are un design unic al benzii de rulare cu spărgătoare speciale de noroi pentru cele mai bune proprietăți de auto-curățare. În plus, canelurile înclinate duble oferă o tracțiune excelentă și o alunecare redusă.

UM

US Standard

Construcție

 BIAS

Mașinării

Agricultură: Tractor

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	9.5 - 24
LI/SS	108 A8

Dimensiuni US Standard

Usa code	94060689
Rating de sarcină	8
Lățimea secțiunii (inch)	9.4
Overall Diameter (inch)	41.3
Static Loaded Radius (inch)	19.3
Rolling Circumference (inch)	125.7
Rim Rec	W 8
Rim Alt	W 7
ECE	E11-106R-005527
TRA Code	R1

Load capacity (lbs)

mph / psi	42
25	2200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 1/15/2025 9:07 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..