

FL 639 - Specificații tehnice



Descriere

FL 639 este o anvelopă radială cu flotație pentru câmp, potrivită și pentru aplicații de împrăștiere. Suprafața sa de amprentă lată asigură compactarea scăzută a solului, rezultând o productivitate crescută a culturilor. Talonul ranforsat și protecția laterală contribuie la un ciclu de viață extins al anvelopei. FL 639 asigură o tracțiune extraordinară împreună cu proprietăți excelente de auto-curățare.

UM

Standard internațional

Construcție

 RADIAL

Mașinării

Agricultură: Mașină de împrăștiat

| | |
|-----------------------|----------------|
| Versiune | STANDARD |
| Tip | TL |
| Dimensiunea anvelopei | 850/40 R 26.5 |
| LI/SS | 173 D / 184 A8 |

Dimensiuni Standard internațional

| | |
|----------------------------|-----------------|
| Lățimea secțiunii (mm) | 860 |
| Overall Diameter (mm) | 1355 |
| Static Loaded Radius (mm) | 599 |
| Rolling Circumference (mm) | 4122 |
| SRI (mm) | 650 |
| Rim Rec | AG 28.00 |
| ECE | E11-106R-006228 |

Load capacity (Kg)

| km/h / bar | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 |
|------------|------|------|------|------|------|------|------|-------|-------|
| 70 | 1895 | 2430 | 3020 | 3435 | 3965 | 4500 | 4910 | 5385 | 5915 |
| 65 | 2080 | 2665 | 3315 | 3770 | 4355 | 4940 | 5395 | 5915 | 6500 |
| 50 | 2520 | 3225 | 4015 | 4565 | 5270 | 5980 | 6530 | 7160 | 7865 |
| 40 | 2880 | 3690 | 4590 | 5220 | 6030 | 6840 | 7470 | 8190 | 9000 |
| 30 | 3145 | 4025 | 5010 | 5695 | 6580 | 7460 | 8150 | 8935 | 9815 |
| 25 | 3290 | 4215 | 5240 | 5960 | 6885 | 7810 | 8525 | 9350 | 10270 |
| 10 | 3745 | 4800 | 5970 | 6790 | 7840 | 8895 | 9715 | 10650 | 11700 |

Imprimat pe 4/27/2024 5:03 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..