

FL 695 - Fișa de date



Descriere

FL 695 a fost proiectată special pentru remorci în aplicații de construcții și transport, cu un model unic al benzii de rulare cu blocuri centrale. Datorită carcasei sale puternice, FL 695 poate transporta sarcini grele menținând stabilitatea în toate condițiile, iar banda de rulare adâncă asigură o auto-curățare optimă în timpul aplicațiilor pe drum și off-road. Straturile din oțel multistratificat oferă protecție împotriva perforărilor.

UM

Standard internațional

Construcție

 RADIAL

Mașinării

Agricultură: Remorcă

Industrial: Remorcă

SIZE	Version	LI/SS	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
600/55 R 26.5	STEEL BELTED	173 D			AG20.00		591	1335	620	4090	625	TL	E11-106R-007937
650/55 R 26.5	STEEL BELTED	178 D			AG20.00	AG22.00	630	1390	630	4242	675	TL	E11-106R-007052
600/60 R 30.5	STEEL BELTED	179 D	179 D	179 D	AG20.00		611	1495	693	4586	725	TL	E11-106R-008503
710/50 R 30.5	STEEL BELTED	177 D	177 D	177 D	AG24.00	AG20.00	700	1490	691	4553	700	TL	E11-106R-008661

Imprimat pe 4/22/2024 6:13 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..