

## FLOTATION 558 - Specificații tehnice



### Descriere

FLOTATION 558 este o anvelopă de flotație cu cută încrucișată, potrivită pentru mașini de recoltat fân/prese de balotat, cisterne și remorci atât pe șosea, cât și în condiții off-road. Este recomandat în special ori de câte ori tracțiunea este esențială pentru o bună lucrare a solului, pe lângă capacitatea mare de încărcare.

### UM

Standard internațional

### Construcție

 BIAS

### Mașinării

Agricultură: Presă de balotat • Mașină de recoltare a fânului • Cisternă • Remorcă

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	500/45 - 22.5
LI/SS DRIVE WHEEL	142 A8/138 B
LI/SS FREE ROLLING	154 A8/150 B

## Dimensiuni Standard internațional

Rating de sarcină	16
Lățimea secțiunii (mm)	500
Overall Diameter (mm)	1045
Static Loaded Radius (mm)	471
Rolling Circumference (mm)	3167
Rim Rec	AG 16.00
ECE	E4-106R-002315

## Load capacity (Kg)

km/h / bar	3.20	3.40	3.60
10 FR	4900	5075	5250
20 FR	4410	4570	4725
30 FR	3920	4060	4200
40 FR	3500	3625	3750
50 FR	3150	3265	3350
10 DW	3465	3590	3710
20 DW	3120	3230	3340
30 DW	2770	2875	2970
40 DW	2475	2565	2650
50 DW	2230	2310	2360

Imprimat pe 12/11/2023 7:14 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..