

FLOTATION 647 - Specificații tehnice



Descriere

FLOTATION 647 este o anvelopă pentru utilaje care oferă cea mai bună tracțiune pe sol moale și pășuni. Pe lângă proprietățile excelente de auto-curățare, modelul special conceput al benzii de rulare oferă o zonă lată de contact, care asigură o presiune optimizată pe sol și o performanță excelentă pe solul moale.

UM

Standard internațional

Construcție

 BIAS

Mașinării

Agricultură: Mașini de implementare

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	520/50 - 17
LI/SS DRIVE WHEEL	147 B
LI/SS FREE ROLLING	159 B

Dimensiuni Standard internațional

Lățimea secțiunii (mm)	516
Overall Diameter (mm)	965
Static Loaded Radius (mm)	426
Rolling Circumference (mm)	2907
Rim Rec	AG 16.00
ECE	E11-106R-005770

Load capacity (Kg)

km/h / bar	4.00
50 FR	4375
50 DW	3075

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 3/26/2025 2:48 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..