

FLOTATION 648 - Specificații tehnice



Descriere

FLOTATION 648 este deosebit de potrivită pentru transportul pe câmp și rutier, precum și pentru operațiuni de împrăștiere. Unele dimensiuni sunt concepute pentru mașini de recoltat fân/prese de balotat. Designul special al benzii de rulare permite transportarea sarcinilor foarte grele la presiune mică, garantând în același timp compactarea redusă a solului și prevenind deteriorarea culturilor.

UM

US Standard

Construcție

 BIAS

Mașinării

Agricultură: Presă de balotat • Mașină de recoltare a fânului • Mașină de împrăștiat

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	350/65 - 22.5
LI/SS DRIVE WHEEL	139 A8/135 B
LI/SS FREE ROLLING	151 A8/147 B

Dimensiuni US Standard

Usa code	94030644
Rating de sarcină	18
Lățimea secțiunii (inch)	14.1
Overall Diameter (inch)	40.6
Static Loaded Radius (inch)	17.8
Rolling Circumference (inch)	120.8
Rim Rec	AG 11.75
ECE	E11-106R-004551

Load capacity (lbs)

mph / psi	29	44	58	73
5 FR	6240	7900	9350	10650
10 FR	5610	7110	8420	9580
20 FR	4980	6320	7480	8520
25 FR	4450	5640	6680	7610
30 FR	4010	5080	6010	6780
5 DW	4390	5560	6590	7500
10 DW	3950	5000	5930	6750
20 DW	3510	4440	5270	6000
25 DW	3130	3970	4710	5360
30 DW	2820	3570	4230	4810

Imprimat pe 4/26/2024 7:35 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..