

FLOTATION 648 - Specificații tehnice



Descriere

FLOTATION 648 este deosebit de potrivită pentru transportul pe câmp și rutier, precum și pentru operațiuni de împrăștiere. Unele dimensiuni sunt concepute pentru mașini de recoltat fân/prese de balotat. Designul special al benzii de rulare permite transportarea sarcinilor foarte grele la presiune mică, garantând în același timp compactarea redusă a solului și prevenind deteriorarea culturilor.

UM

US Standard

Construcție

 BIAS

Mașinării

Agricultură: Presă de balotat • Mașină de recoltare a fânului • Mașină de împrăștiat

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	500/50 - 17
LI/SS DRIVE WHEEL	128 A8/124 B
LI/SS FREE ROLLING	140 A8/136 B

Dimensiuni US Standard

Usa code	94039814
Rating de sarcină	10
Lățimea secțiunii (inch)	20.1
Overall Diameter (inch)	37.2
Static Loaded Radius (inch)	16.4
Rolling Circumference (inch)	108.3
Rim Rec	16.00
ECE	E4-106R-002713

Load capacity (lbs)

mph / psi	22	25	29
5 FR	6530	7020	7720
10 FR	5870	6320	6940
20 FR	5220	5620	6170
25 FR	4660	5020	5510
30 FR	4200	4520	4940
5 DW	4700	5050	5560
10 DW	4220	4540	5000
20 DW	3750	4030	4440
25 DW	3350	3600	3970
30 DW	3020	3240	3530

Imprimat pe 4/26/2024 9:48 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..