

FLOTATION 648 - Specificații tehnice



Descriere

FLOTATION 648 este deosebit de potrivită pentru transportul pe câmp și rutier, precum și pentru operațiuni de împrăștiere. Unele dimensiuni sunt concepute pentru mașini de recoltat fân/prese de balotat. Designul special al benzii de rulare permite transportarea sarcinilor foarte grele la presiune mică, garantând în același timp compactarea redusă a solului și prevenind deteriorarea culturilor.

UM

US Standard

Construcție

 BIAS

Mașinării

Agricultură: Presă de balotat • Mașină de recoltare a fânului • Mașină de împrăștiat

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	550/60 - 22.5
LI/SS DRIVE WHEEL	148 A8/144 B
LI/SS FREE ROLLING	160 A8/156 B

Dimensiuni US Standard

Usa code	94006373
Rating de sarcină	12
Lățimea secțiunii (inch)	21.7
Overall Diameter (inch)	48.8
Static Loaded Radius (inch)	21.3
Rolling Circumference (inch)	146.7
Rim Rec	AG 16.00
ECE	E4-106R-002310

Load capacity (lbs)

mph / psi	22	26	30
5 FR	11410	12690	13890
10 FR	10260	11420	12500
20 FR	9130	10150	11110
25 FR	8150	9060	9920
30 FR	7330	8160	8820
5 DW	7980	8880	9720
10 DW	7180	8000	8750
20 DW	6380	7110	7780
25 DW	5700	6350	6940
30 DW	5130	5710	6170

Imprimat pe 4/26/2024 6:46 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..