

FLOTATION 648 - Specificații tehnice



Descriere

FLOTATION 648 este deosebit de potrivită pentru transportul pe câmp și rutier, precum și pentru operațiuni de împrăștiere. Unele dimensiuni sunt concepute pentru mașini de recoltat fân/prese de balotat. Designul special al benzii de rulare permite transportarea sarcinilor foarte grele la presiune mică, garantând în același timp compactarea redusă a solului și prevenind deteriorarea culturilor.

UM

US Standard

Construcție

 BIAS

Mașinării

Agricultură: Presă de balotat • Mașină de recoltare a fânului • Mașină de împrăștiat

Versiune	HD
Tip	TL
Dimensiunea anvelopei	650/65 - 30.5
LI/SS DRIVE WHEEL	169 A8/165 B
LI/SS FREE ROLLING	181 A8/178 B

Dimensiuni US Standard

Usa code	94030279
Rating de sarcină	18
Lățimea secțiunii (inch)	26.4
Overall Diameter (inch)	65.4
Static Loaded Radius (inch)	28
Rolling Circumference (inch)	194.3
Rim Rec	AG 20.00
ECE	E11-106R-004563

Load capacity (lbs)

mph / psi	33	35	36
5 FR	24240	24860	25460
10 FR	21810	22380	22920
20 FR	19400	19880	20370
25 FR	17320	17760	18190
30 FR	15590	15980	16530
5 DW	17050	17480	17900
10 DW	15340	15740	16110
20 DW	13650	13990	14320
25 DW	12180	12490	12790
30 DW	10970	11240	11350

Imprimat pe 4/26/2024 6:39 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..