

FLOTATION RIB 774 - Specificații tehnice



Descriere

FLOTATION RIB 774 este potrivită pentru toate aplicațiile de rulare liberă, aplicațiile de recoltare a fânului și este ideală pentru remorci. A fost proiectată pentru a oferi cel mai bun confort de manipulare, optimizând timpul de operare, precum și o capacitate mare de încărcare și o durată de viață mai lungă a anvelopei.

UM

Standard internațional

Construcție

 BIAS

Mașinării

Agricultură: Mașină de recoltare • Mașină de recoltare a fânului • Remorcă

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	550/60 - 22.5
LI/SS FREE ROLLING	167 A8/163 B

Dimensiuni Standard internațional

Rating de sarcină	16
Lățimea secțiunii (mm)	550
Overall Diameter (mm)	1240
Static Loaded Radius (mm)	540
Rolling Circumference (mm)	3725
Rim Rec	AG 16.00
ECE	E11-106R-005942

Load capacity (Kg)

km/h / bar	2.40	2.60	2.80
10 FR	6970	7310	7630
20 FR	6275	6575	6865
30 FR	5580	5845	6105
40 FR	4980	5220	5450
50 FR	4480	4700	4875

Imprimat pe 4/25/2024 9:06 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..