

FLOTATION RIB 774 - Specificații tehnice



Descriere

FLOTATION RIB 774 este potrivită pentru toate aplicațiile de rulare liberă, aplicațiile de recoltare a fânului și este ideală pentru remorci. A fost proiectată pentru a oferi cel mai bun confort de manipulare, optimizând timpul de operare, precum și o capacitate mare de încărcare și o durată de viață mai lungă a anvelopei.

UM

Standard internațional

Construcție

 BIAS

Mașinării

Agricultură: Mașină de recoltare • Mașină de recoltare a fânului • Remorcă

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	600/55 - 22.5
LI/SS FREE ROLLING	164 A8/160 B

Dimensiuni Standard internațional

Rating de sarcină	12
Lățimea secțiunii (mm)	600
Overall Diameter (mm)	1230
Static Loaded Radius (mm)	540
Rolling Circumference (mm)	3716
Rim Rec	AG 20.00
ECE	E11-106R-005943

Load capacity (Kg)

km/h / bar	1.50	1.70	2.00
10 FR	5915	6365	7000
20 FR	5325	5725	6300
30 FR	4730	5090	5600
40 FR	4225	4545	5000
50 FR	3805	4090	4500

Imprimat pe 4/23/2024 11:12 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..