

## FLOTATION RIB 774 - Specificații tehnice



### Descriere

FLOTATION RIB 774 este potrivită pentru toate aplicațiile de rulare liberă, aplicațiile de recoltare a fânului și este ideală pentru remorci. A fost proiectată pentru a oferi cel mai bun confort de manipulare, optimizând timpul de operare, precum și o capacitate mare de încărcare și o durată de viață mai lungă a anvelopei.

### UM

Standard internațional

### Construcție

 BIAS

### Mașinării

Agricultură: Mașină de recoltare • Mașină de recoltare a fânului • Remorcă

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	600/55 - 22.5
LI/SS FREE ROLLING	169 A8/166 B

## Dimensiuni Standard internațional

Rating de sarcină	16
Lățimea secțiunii (mm)	600
Overall Diameter (mm)	1230
Static Loaded Radius (mm)	540
Rolling Circumference (mm)	3716
Rim Rec	AG 20.00
ECE	E11-106R-005944

## Load capacity (Kg)

km/h / bar	2.20	2.40	2.60
10 FR	7365	7750	8120
20 FR	6630	6975	7310
30 FR	5890	6200	6495
40 FR	5260	5535	5800
50 FR	4735	4980	5300

Imprimat pe 8/15/2024 1:55 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..