

FLOTATION TR 675 - Specificații tehnice



Descriere

FLOTATION TR 675 este anvelopa ideală pentru transportul pe câmp și rutier. Se potrivește la remorci și utilaje.

FLOTATION TR 675 a fost proiectată pentru a oferi o tracțiune remarcabilă, o capacitate mare de încărcare și o durată de viață mai lungă a anvelopei.

UM

US Standard

Construcție

 BIAS

Mașinării

Agricultură: Mașini de implementare • Remorcă

| | |
|-----------------------|---------------|
| Versiune | STANDARD |
| Tip | TL |
| Dimensiunea anvelopei | 500/60 - 22.5 |
| LI/SS DRIVE WHEEL | 145 A8/142 B |
| LI/SS FREE ROLLING | 157 A8/154 B |

Dimensiuni US Standard

| | |
|------------------------------|----------------|
| Usa code | 94019786 |
| Rating de sarcină | 12 |
| Lățimea secțiunii (inch) | 20.3 |
| Overall Diameter (inch) | 46.5 |
| Static Loaded Radius (inch) | 21.3 |
| Rolling Circumference (inch) | 141.9 |
| Rim Rec | AG 16.00 |
| Rim Alt | 15.00 ; 17.00 |
| ECE | E4-106R-002314 |

Load capacity (lbs)

| mph / psi | 22 | 29 | 35 |
|-----------|------|-------|-------|
| 5 FR | 9680 | 11450 | 12730 |
| 10 FR | 8710 | 10310 | 11460 |
| 20 FR | 7740 | 9160 | 10180 |
| 25 FR | 6910 | 8180 | 9090 |
| 30 FR | 6220 | 7360 | 8270 |
| 5 DW | 6800 | 8040 | 8950 |
| 10 DW | 6130 | 7230 | 8060 |
| 20 DW | 5450 | 6440 | 7160 |
| 25 DW | 4860 | 5740 | 6390 |
| 30 DW | 4380 | 5170 | 5840 |

Imprimat pe 4/27/2024 5:01 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..