FLOTATION TR 678 - Specificații tehnice

Descriere

FLOTATION TR 678 a fost special concepută pentru remorci și utilaje agricole atât pe șosea, cât și în afara acestuia. Această anvelopă permite transportul de sarcini foarte grele la presiune scăzută, asigurând în același timp o compactare redusă a solului. Oferă tracțiune excelentă și proprietăți remarcabile de auto-curățare.

UM

Standard internațional

Construcție

BIAS

Mașinării

Agricultură: Mașini de implementare • Remorcă

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	280/60 - 15.5
LI/SS	115 A8

Dimensiuni Standard internațional

Lățimea secțiunii (mm)	275
Overall Diameter (mm)	750
Static Loaded Radius (mm)	357
Rolling Circumference (mm)	2250
Rim Rec	8.0
ECE	E11-106R-004261

Load capacity (Kg)

km/h / bar	2.40
40	1215

Imprimat pe 4/27/2024 8:18 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..