GIANT TRAX - Specificații tehnice

Descriere

GIANT TRAX a fost proiectată pentru mini-încărcătoare în depozitele de deșeuri, pe suprafețe accidentate de beton, aplicații de reciclare și mine. Banda de rulare foarte adâncă, cu blocuri mai late și mai rezistente, oferă cea mai bună tracțiune, stabilitate și rezistență la perforare. Compusul special al benzii de rulare are ca rezultat o rezistență excepțională la tăiere și așchiere, împreună cu o rezistență excelentă la uzură pe toate tipurile de teren.

UM

Standard internațional

Construcție

BIAS

Mașinării

Industrial: Mini-încărcător

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	12 - 16.5

Dimensiuni Standard internațional

Rating de sarcină	14
Lățimea secțiunii (mm)	315
Overall Diameter (mm)	840
Static Loaded Radius (mm)	398
Rolling Circumference (mm)	2521
Rim Rec	9.75
ECE	E11-106R-005562

Load capacity (Kg)

km/h / bar	6.20
10	3075
15	2430
25	2245

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 10/12/2024 10:49 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..