

GR 288 - Specificații tehnice



Descriere

GR 288 (G-2/L-2) este o anvelopă versatilă cu cute înclinate pentru autogredere sau încărcătoare. Este ideală pentru utilizare în construcții, pregătirea șantierului, construcția de drumuri și alte medii moi sau noroioase. Modelul benzii de rulare cu auto-curățare oferă o tracțiune excelentă și vă puteți aștepta la o durată lungă de viață a anvelopei ca urmare a compusului special rezistent la tăiere și așchiere.

UM

Standard internațional

Construcție

 BIAS

Mașinării

Industrial: Buldozer • Încărcător
OTR: Autogreder

| | |
|-----------------------|-----------|
| Versiune | STANDARD |
| Tip | TL |
| Dimensiunea anvelopei | 17.5 - 25 |

Dimensiuni Standard internațional

| | |
|----------------------------|-----------------|
| Rating de sarcină | 16 |
| Overall Width (mm) | 445 |
| Overall Diameter (mm) | 1330 |
| Static Loaded Radius (mm) | 596 |
| Rolling Circumference (mm) | 3950 |
| Rim Rec | 14.00/1.5 |
| Rim Alt | 14.00/1.3 (DC) |
| ECE | E11-106R-004561 |
| TRA Code | G2/L2 |

Load capacity (Kg)

| km/h / bar | 2.75 | 4.75 |
|------------|------|------|
| 40 | 3350 | - |
| 10 | - | 7300 |

Imprimat pe 4/20/2024 4:00 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..