

GRIP STAR - Specificații tehnice



Descriere

GRIP STAR este o anvelopă agroindustrială pentru aplicații de încărcare cu manipolatoare telescopice. Are proprietăți excelente de tracțiune și auto-curățare. În plus, este o anvelopă pentru orice sezon, potrivită în special pentru operațiuni pe teren noroios. GRIP STAR este, de asemenea, disponibilă într-o versiune „specială” care oferă rezistență suplimentară la tăiere și așchiere.

UM

Standard internațional

Construcție

 BIAS

Mașinării

Industrial: Încărcător telescopic

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	15.5/80 - 24
LI/SS DRIVE WHEEL	151 A6
LI/SS FREE ROLLING	163 A6

Dimensiuni Standard internațional

Rating de sarcină	16
Lățimea secțiunii (mm)	392
Overall Diameter (mm)	1270
Static Loaded Radius (mm)	569
Rolling Circumference (mm)	3683
SRI (mm)	600
Rim Rec	W 12
Rim Alt	W 13 ; W 14 L

Load capacity (Kg)

km/h / bar	4.00
30 FR LLV	4875
30 DW LLV	3450

Imprimat pe 4/26/2024 6:23 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..