

GRIP STAR - Specificații tehnice



Descriere

GRIP STAR este o anvelopă agroindustrială pentru aplicații de încărcare cu manipolatoare telescopice. Are proprietăți excelente de tracțiune și auto-curățare. În plus, este o anvelopă pentru orice sezon, potrivită în special pentru operațiuni pe teren norios. GRIP STAR este, de asemenea, disponibilă într-o versiune „specială” care oferă rezistență suplimentară la tăiere și așchiere.

UM

Standard internațional

Construcție

 BIAS

Mașinării

Industrial: Încărcător telescopic

| | |
|-----------------------|--------------|
| Versiune | SPECIAL |
| Tip | TL |
| Dimensiunea anvelopei | 15.5/80 - 24 |
| LI/SS DRIVE WHEEL | 151 A6 |
| LI/SS FREE ROLLING | 163 A6 |

Dimensiuni Standard internațional

| | |
|----------------------------|---------------|
| Rating de sarcină | 16 |
| Lățimea secțiunii (mm) | 392 |
| Overall Diameter (mm) | 1270 |
| Static Loaded Radius (mm) | 569 |
| Rolling Circumference (mm) | 3683 |
| SRI (mm) | 600 |
| Rim Rec | W 12 |
| Rim Alt | W 13 ; W 14 L |

Load capacity (Kg)

| | |
|------------|------|
| km/h / bar | 4.00 |
| 30 FR LLV | 4875 |
| 30 DW LLV | 3450 |

Imprimat pe 4/26/2024 7:15 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..