

GRIP STAR - Specificații tehnice



Descriere

GRIP STAR este o anvelopă agroindustrială pentru aplicații de încărcare cu manipolatoare telescopice. Are proprietăți excelente de tracțiune și auto-curățare. În plus, este o anvelopă pentru orice sezon, potrivită în special pentru operațiuni pe teren noroios. GRIP STAR este, de asemenea, disponibilă într-o versiune „specială” care oferă rezistență suplimentară la tăiere și așchiere.

UM

US Standard

Construcție

 BIAS

Mașinării

Industrial: Încărcător telescopic

Versiune	SPECIAL
Tip	TL
Dimensiunea anvelopei	15.5/80 - 24
LI/SS DRIVE WHEEL	151 A6
LI/SS FREE ROLLING	163 A6

Dimensiuni US Standard

Usa code	94035977
Rating de sarcină	16
Lățimea secțiunii (inch)	15.4
Overall Diameter (inch)	50
Static Loaded Radius (inch)	22.4
Rolling Circumference (inch)	145
Rim Rec	W 12
Rim Alt	W 13 ; W 14 L

Load capacity (lbs)

mph / psi	58
20 FR LLV	10750
20 DW LLV	7610

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 2/11/2025 11:57 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..