

## I - 1 - Specificații tehnice



### Descriere

I-1 a fost proiectată pentru transportul pe câmp și rutier, precum și pentru operațiuni de prelucrare a solului cu utilaje și remorci. I-1 este o anvelopă de mare viteză care optimizează timpul de deplasare, astfel încât să vă puteți concentra asupra activității de bază. Designul special al benzii de rulare asigură o durată lungă de viață și în condiții grele și dacă există miriște pe câmp.

### UM

US Standard

### Construcție

 BIAS

### Mașinării

Agricultură: Mașini de implementare • Remorcă

Versiune	STUBBLE RESISTANT
Tip	TL
Dimensiunea anvelopei	11L - 15 SL
LI/SS	113 D

## Dimensiuni US Standard

Usa code	94044801
Rating de sarcină	8
Lățimea secțiunii (inch)	10.6
Overall Diameter (inch)	30.3
Static Loaded Radius (inch)	13.5
Rolling Circumference (inch)	88.8
Rim Rec	8 LB
Rim Alt	10 LB
TRA Code	I1

## Load capacity (lbs)

mph / psi	36
40	2540

Imprimat pe 4/19/2024 8:50 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..