I - 1 - Specificații tehnice

Descriere

I-1 a fost proiectată pentru transportul pe câmp și rutier, precum și pentru operațiuni de prelucrare a solului cu utilaje și remorci. I-1 este o anvelopă de mare viteză care optimizează timpul de deplasare, astfel încât să vă puteți concentra asupra activității de bază. Designul special al benzii de rulare asigură o durată lungă de viață și în condiții grele și dacă există mirişte pe câmp.

UM

Standard internațional

Construcție

BIAS

Mașinării

Agricultură: Mașini de implementare • Remorcă

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	9.5L - 15 SL
LI/SS	112 D

Dimensiuni Standard internațional

Rating de sarcină	8
Lățimea secțiunii (mm)	241
Overall Diameter (mm)	765
Static Loaded Radius (mm)	340
Rolling Circumference (mm)	2242
Rim Rec	7.00
Rim Alt	8 LB
ECE	E11-106R-003445
TRA Code	I1

Load capacity (Kg)

km/h / bar	3.00
65	1120

Imprimat pe 5/2/2024 3:51 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..