

## LIFT STAR PLUS - Specificații tehnice



### Descriere

LIFT STAR este o anvelopă cu cută înclinată, special concepută pentru manipuloarele telescopice care operează în construcții solicitante și alte aplicații dificile. Peretele său lateral cu profil jos asigură o stabilitate excelentă în operațiunile de ridicare la înălțime mare, în timp ce designul nedirecțional al benzii de rulare permite o mai mare versatilitate de montare. În plus, peretele lateral special proiectat oferă protecție suplimentară împotriva tăierii și perforării. &nbsp;

### UM

US Standard

### Construcție

❖ BIAS

### Mașinării

Industrial: Încărcător telescopic

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	370/75 - 28

## Dimensiuni US Standard

Usa code	94053001
Rating de sarcină	14
Lățimea secțiunii (inch)	14.4
Overall Diameter (inch)	50
Static Loaded Radius (inch)	23
Rolling Circumference (inch)	151.6
Rim Rec	11.00
ECE	E11-106R-005331

## Load capacity (lbs)

mph / psi	47	73
30	7150	-
5	-	12000

Imprimat pe 11/28/2023 5:41 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..