

LOADER PLUS - Specificații tehnice



Descriere

LOADER PLUS (L-3) este o anvelopă cu cute înclinate, special concepută pentru încărcătoare. Compusul benzii de rulare oferă proprietăți de rezistență la tăiere și așchiere și este optim pentru operațiunile de încărcare și dozare.

UM

US Standard

Construcție



Mașinării

Industrial: Buldozer • Încărcător OTR: Buldozer • Încărcător

| Versiune | STANDARD |
|-----------------------|-----------|
| Тір | TL |
| Dimensiunea anvelopei | 26.5 - 25 |

Dimensiuni US Standard

| Usa code | 94065066 |
|------------------------------|-----------|
| Rating de sarcin ă | 32 |
| Overall Width (inch) | 26.8 |
| Overall Diameter (inch) | 68.5 |
| Static Loaded Radius (inch) | 31.3 |
| Rolling Circumference (inch) | 202.8 |
| Rim Rec | 22.00/3.0 |
| TRA Code | L3 |

Load capacity (lbs)

| mph / psi | 80 |
|-----------|-------|
| 5 | 37500 |

Imprimat pe 4/29/2024 12:11 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..