

LT TR 182 - Specificații tehnice



Descriere

LT TR 182 este potrivită pentru operațiuni de transport pe camioane ușoare. Această anvelopă de mare viteză este destinată deplasării pe șosea și reduce semnificativ consumul de combustibil. Anvelopa LT TR 182 este, de asemenea, ușor de montat.

UM

Standard internațional

Construcție

 BIAS

Mașinării

Industrial: Camion ușor

| | |
|-----------------------|----------|
| Versiune | STANDARD |
| Tip | TL |
| Dimensiunea anvelopei | 8 - 14.5 |

Dimensiuni Standard internațional

| | |
|------------------------|---------|
| Rating de sarcină | 12 |
| Lățimea secțiunii (mm) | 207 |
| Overall Diameter (mm) | 710 |
| Rim Rec | 6.00 MH |

Load capacity (Kg)

| km/h / bar | 6.90 |
|------------|------|
| 100 LS | 1285 |
| 100 LD | 1130 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 10/7/2024 12:22 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..