

MAGLIFT ECO - Specificații tehnice



Descriere

MAGLIFT ECO a fost special concepută pentru stivuitoare. Anvelopa are un model de caneluri late care oferă stabilitate maximă și distribuție optimizată a sarcinii. Structura sa întărită elimină riscurile de alunecare, în timp ce apăraoarea special concepută pentru jantă asigură protecție împotriva deteriorării roților. MAGLIFT ECO prezintă tracțiune excelentă, precum și rezistență scăzută la rulare și căldură redusă acumulată pentru o eficiență îmbunătățită.

UM

US Standard

Construcție

◆ SOLID

Mașinării

Industrial: Stivuator

Versiune

LIP

Tip

Dimensiunea anvelopei

8.25 - 15

Dimensiuni US Standard

Usa code	94064069
Lățimea secțiunii (inch)	8.3
Overall Diameter (inch)	31.8
Rim Rec	6.5 - 15

Load capacity (lbs)

	mph / psi	-
	15 LOAD WHEEL	10470
	15 STEER WHEEL	8045

Imprimat pe 4/26/2024 8:07 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..