

## MAGLIFT GROSS - Specificații tehnice



### Descriere

The new MAGLIFT GROSS has been specially designed for yard tractors and semi-trailer movements in industrial applications, mainly in distribution centers, logistic hubs, container depots.

Its wide tread profile provides great lateral stability and higher safety in lifting and cornering operations even with heavy loads.

MAGLIFT GROSS has been developed with a reinforced structure that eliminates slippage risks, whilst its special bead shape simplifies mounting operations on the rim.

### UM

US Standard

### Construcție

◆ SOLID

### Mașinării

Industrial: Tractor industrial

Versiune	STANDARD
Tip	
Dimensiunea anvelopei	355/50 - 20

### Dimensiuni US Standard

Usa code	94070435
Lățimea secțiunii (inch)	12.2
Overall Diameter (inch)	33.1
Rim Rec	10.00 - 20

## Load capacity (lbs)

mph / psi	-
15 LOAD WHEEL	19775
15 STEER WHEEL	15210

Imprimat pe 4/25/2024 8:25 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..