

## MAGLIFT - Specificații tehnice



### Descriere

MAGLIFT a fost special concepută pentru stivuitoare în operațiuni industriale și logistice. Această anvelopă solidă are o capacitate mare de încărcare și un confort remarcabil. MAGLIFT prezintă o rezistență excelentă la tăiere și așchiere, rezultând o viață lungă a anvelopei. Structura sa întărită elimină riscurile de alunecare, în timp ce forma specială a talonului simplifică operațiunile de montare pe jantă.

### UM

US Standard

### Construcție

◆ SOLID

### Mașinării

Industrial: Stivuator

Versiune

STANDARD - NON MARKING

Tip

Dimensiunea anvelopei

21 X 8 - 9  
(200/75 - 9)

## Dimensiuni US Standard

Usa code	94054558
TMPH	1
Lățimea secțiunii (inch)	7.4
Overall Diameter (inch)	20.7
Rim Rec	6.00 E - 9

## Load capacity (lbs)

	mph / psi	-
15 LOAD WHEEL		6075
15 STEER WHEEL		4675

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 3/19/2025 1:29 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..