

## MAGLIFT - Specificații tehnice



### Descriere

MAGLIFT a fost special concepută pentru stivuitoare în operațiuni industriale și logistice. Această anvelopă solidă are o capacitate mare de încărcare și un confort remarcabil. MAGLIFT prezintă o rezistență excelentă la tăiere și așchiere, rezultând o viață lungă a anvelopei. Structura sa întărită elimină riscurile de alunecare, în timp ce forma specială a talonului simplifică operațiunile de montare pe jantă.

### UM

Standard internațional

### Construcție

◆ SOLID

### Mașinării

Industrial: Stivuator

Versiune

STANDARD - NON MARKING

Tip

Dimensiunea anvelopei

300 - 15  
(315/70 - 15)

## Dimensiuni Standard internațional

Lățimea secțiunii (mm)	255
Overall Diameter (mm)	820
Rim Rec	8.0 - 15

## Load capacity (Kg)

	km/h / bar	-
25 LOAD WHEEL		5850
25 STEER WHEEL		4500

Imprimat pe 4/26/2024 12:10 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..