

MINE STAR - Specificații tehnice



Descriere

MINE STAR este o anvelopă cu straturi diagonale și reprezintă o alegere excelentă pentru operațiunile miniere subterane dificile. Are rezistență ridicată la tăiere/așchiere și la perforare, oferind o eficiență operațională îmbunătățită. MINE STAR este fabricată dintr-un compus special și are un design special al benzii de rulare care are ca rezultat un ciclu de viață prelungit al anvelopei.

UM

Standard internațional

Construcție

 BIAS

Mașinării

OTR: Vehicul pentru exploatare minieră subterană

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	55 X 19.00 - 25

Dimensiuni Standard internațional

Rating de sarcină	50
Lățimea secțiunii (mm)	480
Overall Diameter (mm)	1400
Static Loaded Radius (mm)	632
Rolling Circumference (mm)	4280
Rim Rec	14.00
TRA Code	L5
Tread Depth	69

Load capacity (Kg)

km/h / bar	10.00
5	17305
10	15315
15	14245
25	13020

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 2/13/2025 5:36 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..