

MINEFORCE - Specificații tehnice



Descriere

MINEFORCE este o anvelopă cu structură cu cută înclinată special proiectată pentru autobasculantele folosite în minieră și cariere. Anvelopa de înaltă performanță MINEFORCE pentru autobasculante este răspunsul inovator al societății BKT la zonele miniere stâncoase, abrazive și dure. Are un design unic al benzii de rulare, folosind compuși special dezvoltați pentru condiții de exploatare tari, stâncoase și dure. Patch-ul său de contact mare, sa mare de contact cu caneluri rigide asigură o uzură uniformă a benzii de rulare și un ciclu de viață mai lung.

UM

Standard internațional

Construcție

 BIAS

Mașinării

OTR: Autobasculantă rigidă

Versiune	CUT RESISTANT
Tip	TL
Dimensiunea anvelopei	24.00 - 35

Dimensiuni Standard internațional

Rating de sarcină	48
TKPH	370
Overall Width (mm)	655
Overall Diameter (mm)	2190
Static Loaded Radius (mm)	1003
Rolling Circumference (mm)	6482
Rim Rec	17.00/3.5
TRA Code	E4

Load capacity (Kg)

km/h / bar	6.50	8.50
50	18500	-
10	-	31500

Imprimat pe 4/20/2024 10:41 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..