

MP 567 - Specificații tehnice



Descriere

MP 567 este o anvelopă agroindustrială potrivită pentru transportul pe câmp și rutier și operațiuni municipale/de întreținere. Este anvelopa perfectă pentru manipulatoarele telescopice și utilaje. Anvelopa MP 567 oferă o tracțiune bună în toate condițiile meteorologice, precum și proprietăți excelente de auto-curățare. Această anvelopă asigură o experiență de condus confortabilă, împreună cu o durată de viață mai lungă.

UM

Standard internațional

Construcție

 BIAS

Mașinării

Agricultură: Mașini de implementare • Încărcător telescopic
Industrial: Încărcător telescopic • Vehicul universal

| | |
|-----------------------|----------------|
| Versiune | IMPLEMENT |
| Tip | TL |
| Dimensiunea anvelopei | 10.0/75 - 15.3 |
| LI/SS DRIVE WHEEL | 114 A8 |
| LI/SS FREE ROLLING | 126 A8 |

Dimensiuni Standard internațional

| | |
|----------------------------|-----------------|
| Rating de sarcină | 12 |
| TKPH | 1 |
| Lățimea secțiunii (mm) | 258 |
| Overall Diameter (mm) | 774 |
| Static Loaded Radius (mm) | 365 |
| Rolling Circumference (mm) | 2401 |
| Rim Rec | 9.0 |
| ECE | E11-106R-003527 |

Load capacity (Kg)

| | |
|------------|------|
| km/h / bar | 4.70 |
| 40 FR | 1700 |
| 40 DW | 1180 |

Imprimat pe 4/24/2024 8:38 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..