

## MP 567 - Specificații tehnice



### Descriere

MP 567 este o anvelopă agroindustrială potrivită pentru transportul pe câmp și rutier și operațiuni municipale/de întreținere. Este anvelopa perfectă pentru manipulatoarele telescopice și utilaje. Anvelopa MP 567 oferă o tracțiune bună în toate condițiile meteorologice, precum și proprietăți excelente de auto-curățare. Această anvelopă asigură o experiență de condus confortabilă, împreună cu o durată de viață mai lungă.

### UM

US Standard

### Construcție

 BIAS

### Mașinării

Agricultură: Mașini de implementare • Încărcător telescopic  
Industrial: Încărcător telescopic • Vehicul universal

Versiune	IMPLEMENT
Tip	TL
Dimensiunea anvelopei	11.5/80 - 15
LI/SS DRIVE WHEEL	123 A8
LI/SS FREE ROLLING	135 A8

## Dimensiuni US Standard

Usa code	94054930
Rating de sarcină	12
Lățimea secțiunii (inch)	11.4
Overall Diameter (inch)	34.4
Rim Rec	8 LB
ECE	E11-106R-004621

## Load capacity (lbs)

mph / psi	<b>60</b>
25 FR	4800
25 DW	3420

Imprimat pe 4/24/2024 8:00 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..