

MP 585 - Specificații tehnice



Descriere

MP 585 este o anvelopă agroindustrială, care este potrivită pentru vehiculele multifuncționale în aplicații municipale/de întreținere. Această anvelopă este special concepută cu un model de blocuri care oferă stabilitate și durabilitate maximă în cele mai dificile condiții de lucru, inclusiv la viteze mari.

UM

US Standard

Construcție

 BIAS

Mașinării

Agricultură: Vehicul universal

Industrial: Vehicul universal

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	12.5 - 20

Dimensiuni US Standard

Usa code	94038404
Rating de sarcină	12
Lățimea secțiunii (inch)	13.2
Overall Diameter (inch)	41.3
Static Loaded Radius (inch)	18.9
Rolling Circumference (inch)	123.2
Rim Rec	11
Rim Alt	12 SDC
ECE	E4-54R-0022635

Load capacity (lbs)

	mph / psi	51
	55	4410
	30	4940

Imprimat pe 4/20/2024 8:51 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..