MP 590 - Specificații tehnice

Descriere

MP 590 este o anvelopă agroindustrială potrivită pentru operațiuni de încărcare cu manipulatoare telescopice și stivuitoare. Această anvelopă oferă o tracțiune bună și o stabilitate excelentă, precum și o durabilitate sporită.

UM

Standard internațional

Construcție

BIAS

Mașinării

Agricultură: Încărcător telescopic
Industrial: Stivuitor • Încărcător telescopic • Vehicul universal

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	18 - 22.5 (445/65 - 22.5)

Dimensiuni Standard internațional

Rating de sarcină	20
Lățimea secțiunii (mm)	480
Overall Diameter (mm)	1190
Static Loaded Radius (mm)	530
Rolling Circumference (mm)	3534
Rim Rec	14.0
ECE	E11-106R-004408

Load capacity (Kg)

km/h / bar	7.50
40 DW	5800
30 DW	6500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 10/12/2024 10:54 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..