

MP 600 - Specificații tehnice



Descriere

MP 600 este o anvelopă agroindustrială, potrivită pentru operațiuni municipale/de întreținere cu manipolatoare telescopice și utilaje, oferind o experiență de condus confortabilă. Această anvelopă oferă o tracțiune bună și proprietăți excelente de auto-curățare, împreună cu un ciclu de viață extins al produsului.

UM

US Standard

Construcție

 BIAS

Mașinării

Agricultură: Mașini de implementare • Încărcător telescopic
Industrial: Încărcător telescopic • Vehicul universal

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	400/70 - 24 (16.0/70 - 24)

Dimensiuni US Standard

Usa code	94042043
Rating de sarcină	10
Lățimea secțiunii (inch)	15.9
Overall Diameter (inch)	46.7
Static Loaded Radius (inch)	21.5
Rolling Circumference (inch)	139
Rim Rec	13 SDC
Rim Alt	12

Load capacity (lbs)

mph / psi	36
25 DW	6560
30 DW	6390

Imprimat pe 4/27/2024 9:22 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..