

## MT 612 - Specificații tehnice



### Descriere

MT 612 a fost special concepută pentru utilizare multifuncțională pe și în afara drumului. Carcasa puternică permite transportarea sarcinilor grele la viteză mare, în timp ce canelurile largi oferă o tracțiune remarcabilă. Lățimea suplimentară a benzii de rulare asigură o flotație excelentă pe nisip și noroi. &nbsp; &nbsp;

### UM

US Standard

### Construcție

 BIAS

### Mașinării

Agricultură: Remorcă

Industrial: Vehicul universal

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	14.00 - 20

## Dimensiuni US Standard

Usa code	94029105
Rating de sarcină	18
Lățimea secțiunii (inch)	15.4
Overall Diameter (inch)	49.8
Static Loaded Radius (inch)	23.4
Rolling Circumference (inch)	150.7
Rim Rec	10

## Load capacity (lbs)

mph / psi	96
50 LS	9920
50 LD	8820

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 11/5/2024 7:33 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..