

MULTIMAX MP 513 - Specificații tehnice



Descriere

MULTIMAX MP 513 a fost proiectată de BKT pentru vehicule polivalente în aplicații municipale/întreținere și transport, atât pentru uz agricol, cât și industrial. Este perfectă pentru vehicule universale și camioane cu îngrășămintă. Datorită carcasei puternice din nailon cu benzi din oțel, MULTIMAX MP 513 permite transportarea sarcinilor grele la viteze mari, oferind o experiență de condus confortabilă. Asigură o durată de viață mai lungă și tracțiune, împreună cu proprietăți remarcabile de auto-curățare.

UM

US Standard

Construcție



RADIAL

Mașinării

Agricultură: Vehicul universal • Camion pentru îngrășămintă

Industrial: Vehicul universal

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	285/80 R 16 MPT
LI/SS	128 G

Dimensiuni US Standard

Usa code	94074471
Lățimea secțiunii (inch)	12
Overall Diameter (inch)	34.1
Static Loaded Radius (inch)	15.5
Rolling Circumference (inch)	103
Rim Rec	W 10
ECE	E11-54R-0020958

Load capacity (lbs)

mph / psi	23	29	36	44	51	58
55	1850	2170	2600	3000	3390	3970
40	2000	2350	2800	3230	3660	4290
25	2130	2500	2990	3440	3900	4560

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 6/1/2025 4:40 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..