MULTIMAX MP 513 - Specificații tehnice

Descriere

MULTIMAX MP 513 a fost proiectată de BKT pentru vehicule polivalente în aplicații municipale/întreținere și transport, atât pentru uz agricol, cât și industrial. Este perfectă pentru vehicule universale și camioane cu îngrășăminte. Datorită carcasei puternice din nailon cu benzi din oțel, MULTIMAX MP 513 permite transportarea sarcinilor grele la viteze mari, oferind o experiență de condus confortabilă. Asigură o durată de viață mai lungă și tracțiune, împreună cu proprietăți remarcabile de auto-curățare.

UM

Standard internațional

Construcție

RADIAL

Mașinării

Agricultură: Vehicul universal • Camion pentru îngrășăminte
Industrial: Vehicul universal

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	495/70 R 24 MPT
LI/SS	155 G

Dimensiuni Standard internațional

Lățimea secțiunii (mm)	499
Overall Diameter (mm)	1304
Static Loaded Radius (mm)	588
Rolling Circumference (mm)	3974
Rim Rec	W 16 L
Rim Alt	DW 15 L ; DW 16 L ; W 15 L
ECE	E4-54R-0029057

Load capacity (Kg)

km/h / bar	1.6	2.0	2.5	3.0	3.5
90	1980	2340	2840	3250	3875
65	2150	2540	3085	3530	4205
40	2280	2695	3270	3740	4460

Imprimat pe 4/28/2024 6:17 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..