

MULTIMAX MP 515 - Fișa de date



Descriere

MULTIMAX MP 515 este o anvelopă radială agroindustrială concepută pentru vehicule universale și camioane cu îngrășămintă. Este potrivită pentru aplicații municipale și de transport. Anvelopa prezintă un design unic al benzii de rulare, oferind un confort superior de rulare pe șosea, precum și proprietăți excelente de auto-curățare și tracțiune excelentă. Carcasa puternică din nailon cu bandă de oțel și muchia ranforsată asigură o durabilitate extraordinară. MULTIMAX MP 515 este anvelopa perfectă și la viteze mari (90 km/h).

UM

Standard internațional

Construcție

 RADIAL

Mașinării

Agricultură: Vehicul universal • Camion pentru îngrășămintă

SIZE	Version	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
405/70 R 20 MPT	STANDARD	136 G	13	13 SDC ; 12 SDC ; 11 SDC ; 11	407	1076	493	3286	TL	E4-54R-0016565
425/75 R 20 MPT	STANDARD	148 G	13	13 SDC ; 11 SDC ; 12 SDC ; 11 ; 12	421	1146	522	3491	TL	E11-54R-0017872
445/65 R 22.5 MPT	STANDARD	160 G	13	14	444	1150	527	3532	TL	E11-54R-0017868

Imprimat pe 4/20/2024 12:34 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..