

MULTIMAX MP 519 - Specificații tehnice



Descriere

MULTIMAX MP 519 este o anvelopă potrivită mai ales pentru camioanele ușoare în toate aplicațiile de transport. Carcasa cu bandă din oțel oferă o stabilitate excelentă la viteză mare (90 km/h - 60 mph). Datorită rezistenței sale scăzute la rulare, anvelopa asigură un consum redus de combustibil.

UM

Standard internațional

Construcție

 RADIAL

Mașinării

Industrial: Camion ușor

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	7.50 R 16 LT
LI/SS	112/110G

Dimensiuni Standard internațional

Rating de sarcină	8
Lățimea secțiunii (mm)	220
Overall Diameter (mm)	810
Static Loaded Radius (mm)	377
Rolling Circumference (mm)	2449
Rim Rec	6.00
Rim Alt	5.50 F ; 6 L ; 7 L
ECE	E11-54R-0019046

Load capacity (Kg)

	km/h / bar	3.5
	90 LS	1120
	90 LD	1060

Imprimat pe 4/25/2024 11:32 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..