

## MULTIMAX MP 540 - Specificații tehnice



### Descriere

MULTIMAX MP 540 a fost proiectată de BKT pentru toate vehiculele multifuncționale. Datorită carcasei complet din oțel, MULTIMAX MP 540 permite transportul de sarcini grele în timpul aplicațiilor pe șosea și off-road. În plus, designul cu model în bloc asigură o stabilitate și o durabilitate remarcabile.

### UM

US Standard

### Construcție

 RADIAL

### Mașinării

Agricultură: Vehicul universal

Industrial: Vehicul universal

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	315/55 R 16
LI/SS	120 K / 124 F

## Dimensiuni US Standard

Usa code	94068999
Overall Width (inch)	12
Overall Diameter (inch)	29.6
Static Loaded Radius (inch)	13.9
Rolling Circumference (inch)	91.5
Rim Rec	W10L
Rim Alt	11
ECE	E11-54R-0019558

## Load capacity (lbs)

mph / psi	58
68	3085
50	3520

Imprimat pe 4/26/2024 9:44 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..