

MULTIMAX MP 540 - Specificații tehnice



Descriere

MULTIMAX MP 540 a fost proiectată de BKT pentru toate vehiculele multifuncționale. Datorită carcasei complet din oțel, MULTIMAX MP 540 permite transportul de sarcini grele în timpul aplicațiilor pe șosea și off-road. În plus, designul cu model în bloc asigură o stabilitate și o durabilitate remarcabile.

UM

US Standard

Construcție

 RADIAL

Mașinării

Agricultură: Vehicul universal

Industrial: Vehicul universal

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	405/70 R 24 (16.0/70 R 24)
LI/SS	152 J

Dimensiuni US Standard

Usa code	94074600
Overall Width (inch)	15.8
Overall Diameter (inch)	46.2
Static Loaded Radius (inch)	20.9
Rolling Circumference (inch)	141.2
Rim Rec	13
ECE	E11-54R-0020862

Load capacity (lbs)

mph / psi	73
62	7830

Imprimat pe 4/26/2024 5:35 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..