



PL 801 a fost special concepută pentru aplicații de recoltare a fânului cu mașini de întors fânul/fânătoare și pentru operațiuni logistice cu stivuitoare. Are stabilitate excelentă, precum și rezistență ridicată la tăiere și aşchiere. PL 801 asigură un ciclu de viață extins al anvelopei.

UM

Standard internacional

Construcție



Maşinării

Agricultură: Mașină de recoltare a fânului • Mașină de
întors fânul/Fânător • Stivuitor
Industrial: Stivuitor

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	5.00 - 8

Dimensiuni Standard internațional

Rating de sarcină	8
Lățimea secțiunii (mm)	135
Overall Diameter (mm)	468
Rim Rec	3.00 D
Rim Alt	3.25 I
ECE	E11-106R-003381

Load capacity (Kg)

km/h / bar	8.30
25 LOAD WHEEL	1235
25 STEER WHEEL	950
10 OTHER VEHICLES	1235
25 OTHER VEHICLES	950
STATIC SIDE LOADER	1435

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 5/9/2025 9:21 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..