

## PL 801 - Specificații tehnice



### Descriere

PL 801 a fost special concepută pentru aplicații de recoltare a fânului cu mașini de întors fânul/fânătoare și pentru operațiuni logistice cu stivuitoare. Are stabilitate excelentă, precum și rezistență ridicată la tăiere și aşchieri. PL 801 asigură un ciclu de viață extins al anvelopei.

### UM

Standard internațional

### Construcție

❖ BIAS

### Mașinării

Agricultură: Mașină de recoltare a fânului • Mașină de

întors fânul/Fânător • Stivuitor

Industrial: Stivuitor

Versiune	SPECIAL
Tip	TT
Dimensiunea anvelopei	6.00 - 9

## Dimensiuni Standard internațional

Rating de sarcină	10
Lățimea secțiunii (mm)	157
Overall Diameter (mm)	543
Rim Rec	4.00 E

## Load capacity (Kg)

km/h / bar	8.50
25 LOAD WHEEL	1715
25 STEER WHEEL	1320
10 OTHER VEHICLES	1715
25 OTHER VEHICLES	1320
STATIC SIDE LOADER	1995

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 5/11/2025 10:21 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..