

POWER RIB F2 - Specificații tehnice



Descriere

POWER RIB F2 a fost special concepută pentru tractoare 2WD în aplicații de cultivare a solului. Această anvelopă pentru câmp este potrivită în special pentru toate operațiunile în care sunt necesare performanțe excelente de direcție.

UM

US Standard

Construcție

 BIAS

Mașinării

Agricultură: Tractor 2WD

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	11L - 15 SL
LI/SS	106 A8

Dimensiuni US Standard

Usa code	94020430
Rating de sarcină	8
Lățimea secțiunii (inch)	11
Overall Diameter (inch)	32
Static Loaded Radius (inch)	14.7
Rolling Circumference (inch)	95.4
Rim Rec	8 LB
Rim Alt	10 LB
ECE	E11-106R-004652
TRA Code	F2

Load capacity (lbs)

mph / psi	44
25	2090

Imprimat pe 4/19/2024 3:20 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..