

POWER TRAX HD (FL) - Specificații tehnice



Descriere

POWER TRAX HD este o anvelopă premium cu cută înclinată care este special concepută pentru echipamentele cu stivuitoare în aplicații industriale. Banda de rulare adâncă, peretele lateral extra gros și carcasa rezistentă oferă o durabilitate excepțională, minimizând riscul de perforare și deteriorări accidentale. Anvelopa are o rezistență excelentă la tăiere, așchiere și rupere, potrivită pentru suprafețele neregulate și dure din beton. Apărătoarea special concepută pentru jantă asigură protecție împotriva penelor și a deteriorării roților în zona flanșei jantei.

UM

Standard internațional

Construcție

 BIAS

Mașinării

Industrial: Stivuator

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	6.50 - 10

Dimensiuni Standard internațional

Rating de sarcină	12
Lățimea secțiunii (mm)	193
Overall Diameter (mm)	595
Static Loaded Radius (mm)	278
Rolling Circumference (mm)	1774
Rim Rec	5.00 F
Rim Alt	5.50 F

Load capacity (Kg)

km/h / bar	9.00
25 LOAD WHEEL	2145
25 STEER WHEEL	1650
10 OTHER VEHICLES	2145
25 OTHER VEHICLES	1650
STATIC SIDE LOADER	2490

Imprimat pe 4/23/2024 2:42 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..