POWER TRAX HD (SS) - Specificații tehnice

Descriere

Anvelopa premium POWER TRAX HD este special concepută pentru echipamente în aplicații miniere portuare și subterane. Banda de rulare adâncă, peretele lateral extra gros și carcasa rezistentă oferă o durabilitate excepțională, minimizând riscul de perforare și deteriorări accidentale. Anvelopa are o rezistență excelentă la tăiere și așchiere, care este deosebit de potrivită pentru suprafețe dure și accidentate. Apărătoarea special concepută pentru jantă asigură protecție împotriva penelor și a deteriorării roților în zona flanșei jantei.

UM

US Standard

Construcție

BIAS

Mașinării

Industrial: Mini-încărcător

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	12 - 16.5

Dimensiuni US Standard

Usa code	94017393
Rating de sarcină	14
Lățimea secțiunii (inch)	12.8
Overall Diameter (inch)	34.1
Static Loaded Radius (inch)	15.4
Rolling Circumference (inch)	100.5
Rim Rec	9.75
ECE	E11-106R-005562

Load capacity (lbs)

mph / psi	90
5	6780
10	5360
15	4950

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 10/12/2024 10:55 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..