

## PRO RIB F2M - Specificații tehnice



### Descriere

PRO RIB F2M este o anvelopă agricolă pentru tractoare 2WD în aplicații de cultivare a solului. Este potrivită cu precădere pentru toate operațiunile care necesită un nivel ridicat de manipulare.

### UM

Standard internațional

### Construcție

 BIAS

### Mașinării

Agricultură: Tractor 2WD

Industrial: Remorcă

Versiune	INDUSTRIAL
Tip	TT
Dimensiunea anvelopei	11.00 - 16 SL
LI/SS	114 A8

## Dimensiuni Standard internațional

Rating de sarcină	8
Lățimea secțiunii (mm)	335
Overall Diameter (mm)	950
Static Loaded Radius (mm)	440
Rolling Circumference (mm)	2830
Rim Rec	10 LB
Rim Alt	W 8 L ; 8 LB
ECE	E11-106R-005291
TRA Code	F2M

## Load capacity (Kg)

km/h / bar	2.80
40	1180

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 4/23/2025 12:51 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..