

## PRO RIB F2M - Specificații tehnice



### Descriere

PRO RIB F2M este o anvelopă agricolă pentru tractoare 2WD în aplicații de cultivare a solului. Este potrivită cu precădere pentru toate operațiunile care necesită un nivel ridicat de manipulare.

### UM

US Standard

### Construcție

 BIAS

### Mașinării

Agricultură: Tractor 2WD

Industrial: Remorcă

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	14L - 16.1 SL
LI/SS	127 A8

## Dimensiuni US Standard

Usa code	94020485
Rating de sarcină	12
Lățimea secțiunii (inch)	14
Overall Diameter (inch)	38.6
Static Loaded Radius (inch)	17.8
Rolling Circumference (inch)	115
Rim Rec	W 11 C
ECE	E4-106R-002331
TRA Code	F2M

## Load capacity (lbs)

mph / psi	52
25	3860

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 4/23/2025 1:15 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..