

PUDDLE SPECIAL (A) - Specificații tehnice



Descriere

PUDDLE SPECIAL este o anvelopă agricolă R-2 special concepută pentru operațiuni pe câmpurile de orez. Designul foarte adânc al benzii de rulare, împreună cu modelul special de caneluri, oferă cea mai bună aderență și tracțiune excelentă chiar și pe sol umed și moale. Bara centrală lată oferă o adaptabilitate mai bună pentru aplicațiile rutiere și oferă performanțe extraordinare de service. În plus, PUDDLE SPECIAL prezintă caracteristici superioare de auto-curățare și durabilitate excelentă.

UM

Standard internațional

Construcție

❖ BIAS

Mașinării

Agricultură: Tractor

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	11 - 32
LI/SS	111 A2

Dimensiuni Standard internațional

Rating de sarcină	6
Lățimea secțiunii (mm)	305
Overall Diameter (mm)	1465
Static Loaded Radius (mm)	702
Rolling Circumference (mm)	4384
Rim Rec	W 10
Rim Alt	W 9
ECE	E11-106R-004096
TRA Code	R2+

Load capacity (Kg)

km/h / bar	1.60
10	1080

Imprimat pe 4/27/2024 5:22 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..